

AUSEAL PTY LTD

SAME DAY PRIMER SEALER – **DO NOT DILUTE**

SAME DAY PRIMER SEALER is a concrete sealant specifically formulated for sealing and protecting freshly poured (sufficiently hard able to be walked on) green concrete surfaces. An additional coat of **AUSEAL CLEAR SEALER** is recommended for optimum performance. **SAME DAY PRIMER SEALER** is based on 100% acrylic copolymer.

FEATURES

- [] Excellent durability – good UV stability
- [] Excellent Water Resistance
- [] Reduces Efflorescence
- [] Suitability for both Interior and Exterior application.
- [] Low tyre marking characteristics
- [] Good abrasion resistance
- [] Curing aid for Concrete.

COLOUR RANGE: Available in Clear.

APPLICATION: Suitable for application by broom, roller or airless spray to freshly poured concrete.

COVERAGE: 5 – 7 Square metres per litre depending on profile and porosity of surface.

SPECIFICATION:

Application Temperature	min. 8 deg C max. 28 deg C
Recoat Time	Min. 24 Hrs – 28 Days
Full Film Formation (Cure)	7 Days.

PACKAGING AND SAFETY: **SAME DAY PRIMER SEALER** is available in 10, 20 and 200 litre drums.
Refer to the Safety Data Sheet before handling or use.

AUSEAL PTY. LTD. – Manufacturers and Suppliers of Protective and Decorative Sealants and Coatings to the Concrete Industry.

25 – 29 Pelson Court, Dandenong South 3175.

Tel: (03) 8787 8388 Email: info@auseal-curite.com.au

DIRECTIONS FOR SURFACE PREPARATION AND APPLICATION

SURFACE PREPARATION

All surfaces to be sealed or coated must be free from dust, dirt, oil, grease and other contaminants.

APPLICATION

Stir thoroughly before and during application to ensure uniformity, making sure that any suspended pigment (if coloured) is completely re-incorporated.

Apply coating **evenly** with broom, roller or spray gun. Uneven application may result in blistering.

Allow recommended drying time and apply evenly **without dilution**.

CLEANING

SAME DAY PRIMER SEALER can be removed from tools and equipment with Auseal Solvent.

PRECAUTIONS

1. **SAME DAY SEAL PRIMER SEALER IS A COMBUSTIBLE LIQUID.**
2. Provide adequate ventilation during application and drying.
3. Store away from naked flames and sparks.
4. Ensure you are familiar with SDS prior to usage.

AUSEAL PTY. LTD. – Manufacturers and Suppliers of Protective and Decorative Sealants and Coatings to the Concrete Industry.

25 – 29 Pelson Court, Dandenong South 3175.

Tel: (03) 8787 8388 Email: info@auseal-curite.com.au